

Dialatrol™ 4 Channel Phone Dialer



Picture not to scale

Please note: If you require a feature not shown, please contact the factory for a customized quotation at (904) 693-3318 or Sales@Suncoast-hyd-elect.com.

Standard Features:

- NEMA 4X Fiberglass enclosure
- Up to 24 hour (estimated) battery backup
- Individually program up to 4 separate input channels with enable/ disable, entry/ exit delay and activation options (N.O. or N.C.). Further customize each channel delay times, telephone/ pager numbers and specific outgoing messages.
- Busy line and no-answer detection
- Up to 4 pre-recorded messages delivered sequentially to 8 different phones, pagers, etc.
- Local or long distance calls transmitted
- Selectable 1-9 calling efforts for numbers dialed.
- Selectable 1-3 message repeats
- Record a variable combination (maximum of 7) of instructional outgoing messages
- 1 year warranty

Dialer Engineering Specifications

Power source:	9-18VDC
Current (OPERATE mode – standby):	28mA typical
Current (OPERATE mode – dialing):	100mA max
Activation:	1) N.C. Activation: dialer activates when an “open” is detected 2) N.O. Activation: dialer activates when a “close” is detected 3) Voltage Activation: N.C. (applied voltage: Min. +5VDC, Max. +28VDC) N.O. (loss of continuous voltage: Min. 0VDC, Max. 0.25VDC)
Max. digits for outgoing numbers:	50
Operating temperature range:	-18 to 55 C (0 to 130 F)
Dimensions (inches):	6 x 4 x 1.5 in
Weight (ounces):	10 oz
Mounting:	Wall or Flat Surface
Case Material:	ABS
Color:	White



136 N. Ellis Road
Jacksonville, FL 32254

Phone: 904-693-3318
Fax: 904-693-3203

Web: <http://www.Suncoast-hyd-elect.com>